

PRODUCT DATA SHEET

Sika ViscoFlow[®]-1994 NG

DESCRIPTION

Sika ViscoFlow[®] 1994 is an improved, new generation, non-chlorinated, acrylic copolymer superplasticizer / high-range water-reducing and slump-retaining admixture.

USES

Sika ViscoFlow[®] 1994 is used for concrete in precast plants, on site and for ready mix concrete. ViscoFlow[®] 1994 is used for concrete that need to be transported over long distance or with extended application time.

ViscoFlow[®] 1994 is added for production of:

- Plastic to fluid concrete.
- Low W/C ratio concrete with or without silica fume.
- Concrete with high water reduction (up to 35%) and improved strength.
- Concrete with air entraining

FEATURES

ViscoFlow[®] 1994 combines several actions. Adsorption to the surface and separation of fines particles by steric hindrance during the hydration process give the following properties:

- Extended workability.
- High water reduction (consequently high water-proofing and resistances).
- High fluidity (consequently easier application).
- High short term resistance.
- High waterproofing improvement.
- Better creeps and shrinkage behaviour.
- Lower carbonation speed.

ViscoFlow[®] 1994 does not contain any chloride or other component which could cause or increase steel corrosion. It can be used without restriction for reinforced or prestressed concrete constructions

PRODUCT INFORMATION

PRODUCT DATA SHEET

Sika ViscoFlow[®]-1994 NG
March 2024, Version 01.01
021301011000004068

Composition	PCE
Packaging	Bulk, 1000 litre Container, 200 litre Drum, 25 litre Keg.
Shelf life	12 months minimum from production date if stored properly in original unopened, sealed and undamaged packaging.
Storage conditions	Store in a dry area between 5°C and 35 °C. Protect from direct sunlight.
Appearance and colour	Light Yellow
Density	1.08 +/- 0.01
pH-Value	4 +/- 1
Total chloride ion content	< 0.1%
Recommended dosage	0.2 to 2% of the cement weight depending on performances required. Usual dosage: 0.4 to 1.5% of the binder weight.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika® products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, must be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the Product Data Sheet for the product concerned, copies of which will be supplied on request or accessed on the Internet under nga.sika.com.

SIKA MANUFACTURING NIGERIA LIMITED

10, Western Industrial Avenue, Isheri
Riverview Estate
Lagos - Ibadan Expressway, Ogun State
NIGERIA
Web: nga.sika.com

SikaViscoFlow-1994NG-en-NG-(03-2024)-1-1.pdf

PRODUCT DATA SHEET
Sika ViscoFlow®-1994 NG
March 2024, Version 01.01
021301011000004068

