

## SYSTEM DATA SHEET

# Sikafloor® EasyFinish CS-30

Highly durable concrete flooring system based on dry-shake hardeners and a special finishing aid

### DESCRIPTION

Sikafloor® EasyFinish CS-30 is a concrete flooring system based on dry-shake hardeners and a specially-designed finishing aid. The patented method enables the application of multiple layers of dry-shake. The finishing aid provides more reliable surface finishing, densifies, and improves surface hardness.

### USES

Sikafloor® EasyFinish CS-30 is used for:

- Medium to heavy wear new concrete floors
- Sikafloor® EasyFinish CS-30 is used for the following application areas:
- Car park decks
- Loading ramps
- Logistics facilities and warehouses
- Manufacturing facilities and workshops
- Storage areas
- Industrial buildings

- Wood processing industry
- Automotive facilities
- Commercial and public buildings
- Railway and metro stations
- Agricultural facilities
- Mining and metal processing facilities
- Recycling plants

Please note:

- The System may only be used by experienced professionals.

### FEATURES

- Very good mechanical and wear resistance
- Cost-effective
- Separate liquid hardener not needed after application
- Reduced moisture loss in early phase
- Easy application and finishing
- Quality improved final finish
- Increased resistance to oils and grease
- Wide range of colours available

### SYSTEM INFORMATION

System structure	Layer	Product
	Dry shake hardener	Sikafloor®-3 QuartzTop Sikafloor®-2 SynTop Sikafloor®-1 MetalTop Sika® Chapdur®
	Finishing aid	Sikafloor®-931 Finishing Aid
	Sealer	Sikafloor® ProSeal Sikafloor® ProSeal W
Colour	Available in a range of colours. Please contact Sika customer service for availability.	
Nominal thickness	2.5–4 mm	

# TECHNICAL INFORMATION

Abrasion resistance	System	Result
	Concrete C25/30 w/c ratio 0.55	reference
	Concrete C25/30 w/c ratio 0.55 + Sikafloor® EasyFinish CS-30	20 % less wear

## APPLICATION INFORMATION

Consumption	Layer	Product	Consumption
	Dry shake hardener	Sikafloor®-3 QuartzTop Sikafloor®-2 SynTop Sikafloor®-1 MetalTop Sika® Chapdur®	4–6 kg/m <sup>2</sup>
	Finishing aid	Sikafloor®-931 Finishing Aid	25–50 g/m <sup>2</sup> per application
	Sealer	Sikafloor® ProSeal Sikafloor® ProSeal W	100–200 g/m <sup>2</sup> per coat

## PRODUCT INFORMATION

### Packaging

### Shelf life

### Storage conditions

## BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## FURTHER DOCUMENTATION

- Individual Product Data Sheets
- Sika Method Statement 850 84 23 Sikafloor® EasyFinish CS-30, Sikafloor® CreamPolish CS-31, Sikafloor® Terrazzo CS-32

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

SIKA MANUFACTURING NIGERIA LIMITED  
10, Western Industrial Avenue, Isheri  
Riverview Estate  
Lagos - Ibadan Expressway, Ogun State  
NIGERIA  
Web: [nga.sika.com](http://nga.sika.com)

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SikafloorEasyFinishCS-30-en-NG-(01-2026)-3-1.pdf

SYSTEM DATA SHEET  
Sikafloor® EasyFinish CS-30  
January 2026, Version 03.01  
02081590000000014