

PRODUCT DATA SHEET

Sika® SealTape S

Elastic waterproof sealing tape for detailing in wet tiled areas

DESCRIPTION

Sika® SealTape S is an elastic waterproof sealing tape with a woven bonding mesh on each surface and an elastic expansion zone in the centre and is used for waterproofing movement and connection joints. The product is a component of a complete sealing system used in conjunction with a waterproofing membrane, tile adhesive and ceramic tiles to achieve a waterproof finish in wet rooms and around wet areas. Internal and external use.

USES

- Sealing perimeter connection joints under tiles in residential or commercial wet rooms and on terraces and balconies
- Sealing all types of joints in vertical and horizontal positions such as: static, movement, connection, construction, corners and around pipe entries

FEATURES

- High elasticity
- Waterproof
- Chemical resistant
- Easy to install
- Service temperature: -25 °C to +60 °C

CERTIFICATES AND TEST REPORTS

- Water Tightness Sika® SealTape S, Säurefliesner-Vereinigung e.V. and Institute for wall and floor finishes, Certificate No. 60210601.001

PRODUCT INFORMATION

Composition	Tape	Thermoplastic elastomer
	Reinforcement	Polyester woven fabric
Packaging	Tape roll and preformed sections	Packaging
	Tape roll	10 m roll 50 m roll 1 roll per carton box
	Internal corners 90°	IC, 10 pcs per sleeve 5 sleeves per carton
	External corners 270°	OC, 10 pcs per sleeve 5 sleeves per carton
	Wall flashings 120 × 120 mm	WF, 2 pcs per sleeve 70 sleeves per carton
	Floor flashings 300 × 300 mm	FF, 2 pcs per carton 20 cartons per box
	Refer to current price list for packaging variations	
Shelf life	36 months from date of production	

Storage conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +40 °C. Always refer to packaging
Appearance and colour	Colour: yellow
Length	10 or 50 m
Width	120 mm
Thickness	~0,6 mm

SYSTEM INFORMATION

System structure	Ancillary adhesive bonding products: <ul style="list-style-type: none"> ▪ SikaTop® Seal-107: Cementitious waterproofing slurry For other similar Sika® products that may also be suitable for use with Sika® SealTape S, contact local Sika Technical Services Department.
-------------------------	---

TECHNICAL INFORMATION

Elongation	Cross: 300 %	(ISO 527-1)
Tear strength	Cross: > 2,0 MPa	(ISO 527-1)
Service temperature	-25 °C to +60 °C. In both dry and wet conditions.	
Foldability at low temperature	No cracks at -20 °C	(DIN 53363)
Watertightness	3 bar	(DIN 1048/5)
Water-vapour transmission rate	1,5 bar	(DIN EN 1928 version B)
Chemical resistance	Resistant to many chemicals. Contact Sika Technical Services for additional information.	

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

- Sika® SealTape S is not suitable for swimming pools, use Sika® SealTape F.
- For sealing movement joints, contact Sika Technical Services for additional information.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the

European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

Refer to the individual Product Data Sheet for the adhesive sealing and bedding Sika® mortar.

SUBSTRATE PREPARATION

Refer to the individual Product Data Sheet for the adhesive sealing and bedding Sika® mortar.

APPLICATION METHOD / TOOLS

Reference must be made to further documentation where applicable, such as relevant method statement, application manual and installation or working instructions.

1. Apply the mixed adhesive sealing and bedding Sika® mortar (i.e. SikaTop® Seal-107) on both sides of the joint/ edge, leaving ~10 mm on both sides of the edge free from mortar.
2. Place the Sika® SealTape-S on the coated joint/ edge and press the tape firmly into the mortar.
3. Cover the tape completely with the adhesive waterproofing mortar (SikaTop® Seal-107).
4. Continue tiling application with the appropriate tile adhesive and grout.

For sealing corners, around taps and pipe penetrations, use the specially designed Sika® SealTape S corner profiles (internal and external corners and pipe collars).

Tape joints:

Tapes can be bonded together with SikaBond® AT Universal Adhesive Sealant. Overlaps must be at least 40 mm. Cover the entire tape joint with Sika adhesive® waterproofing mortar.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA MANUFACTURING NIGERIA LIMITED

10, Western Industrial Avenue, Isheri
Riverview Estate
Lagos - Ibadan Expressway, Ogun State
NIGERIA
Web: nga.sika.com

PRODUCT DATA SHEET

Sika® SealTape S
March 2024, Version 02.01
02179020620000009

SikaSealTapeS-en-NG-(03-2024)-2-1.pdf