

## PRODUCT DATA SHEET

# Sika® Antisol E NG

### CONCRETE CURING AGENT

#### DESCRIPTION

Sika® Antisol® E is a ready to use spray applied liquid curing agent to prevent water loss from the surface of freshly placed concrete. It forms a thin film barrier on the concrete without affecting the normal setting action.

#### USES

Large areas of exposed concrete such as:

- Roads and Highways
- Runways
- Roof decks
- Hangars and loading areas
- Retaining walls
- Pre-stressed structures
- Irrigation channels
- Civil Engineering structures
- Industrial floor slabs

#### FEATURES

- Generally improves the surface appearance
- Reduces cracking
- Ensures achievement of required strengths
- Reduces shrinkage
- Controls cement hydration
- Reduces dust formation
- Improves freeze / thaw resistance
- Alleviates other costly curing methods.

#### CERTIFICATES AND TEST REPORTS

According to ASTM C 309-81 type 1 class A

#### PRODUCT INFORMATION

<b>Packaging</b>	<ul style="list-style-type: none"><li>▪ 25 kg container</li><li>▪ 200 kg drum</li><li>▪ 1000 kg IBC</li></ul>
------------------	---

#### PRODUCT DATA SHEET

Sika® Antisol E NG

December 2024, Version 01.01

021405031000000170

<b>Shelf life</b>	12 months from date of production.
<b>Storage conditions</b>	The product must be stored in original, unopened and undamaged sealed packaging at temperatures between +5 °C and +35 °C. Protect from frost. Always refer to packaging.
<b>Appearance</b>	Whitish emulsion.
<b>Consumption</b>	0,15–0,20 kg/m <sup>2</sup> Consumption depends on wind speed, temperature and humidity during application. These figures are theoretical and do not allow for any additional material due to surface porosity, surface profile, variations in level or wastage etc.

## BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ately after use. Hardened / cured material can only be mechanically removed.

## IMPORTANT CONSIDERATIONS

To prevent the nozzle from blocking, regularly clean the spraying equipment during application.

- After application protect from rain for at least 2–3 hours, depending on the ambient conditions.
- Sika® Antisol® E must be removed before the application of any additional screed or coating.
- The on-time application of Sika® Antisol® E will reduce the plastic shrinkage reducing thus the quantity of the evaporating water from the concrete's mass.

In general, the curing compounds cannot prevent cracking that maybe induced due to long-term concrete shrinkage.

Because of that, it is recommended to design properly joints (shrinkage and expansion joints), as well as comply with the relative production rules and norms that apply for production and curing of concrete.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY / PRE-TREATMENT

Concrete surface must be free from surface water. Evaporation of the surface water can take from 30 mins to 2 hours, depending on temperature and water/ cement ratio.

### EQUIPMENT

Hand type backpack or motorized sprayers Suitability of equipment should be approved before using for full application.

Removal of fresh remnants from tools and application equipment can be carried out using gasoline immedi-

#### PRODUCT DATA SHEET

Sika® Antisol E NG  
December 2024, Version 01.01  
021405031000000170

## APPLICATION

Stir thoroughly before use to ensure full dispersion of solids.

Spray product in a fine mist to completely cover the concrete surface.

Maintain the pressure in the application equipment to ensure a consistent spray.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA MANUFACTURING NIGERIA LIMITED

10, Western Industrial Avenue, Isheri

Riverview Estate

Lagos - Ibadan Expressway, Ogun State

NIGERIA

Web: [nga.sika.com](http://nga.sika.com)

### PRODUCT DATA SHEET

Sika® Antisol E NG

December 2024, Version 01.01

021405031000000170

SikaAntisolENG-en-NG-(12-2024)-1-1.pdf