

**BUILDING TRUST** 

# PRODUCT DATA SHEET Sika<sup>®</sup> Intraplast<sup>®</sup> Z CO

Expansion generating admixture and plasticizer for pastes, mortars or grouts of cementitious materials

#### DESCRIPTION

Sika<sup>®</sup> Intraplast<sup>®</sup> Z CO is a finely ground powder additive that generates expansion and plasticizes the mixes of mortar, mortar or grout of cementitious materials. Does not contain chlorides.

#### USES

**Sika® Intraplast® Z CO** is used to increase fluidity and control the contraction of pastes, mortars and grouts in contact and consolidation injections such as:

- Post-tensioned cable ducts.
- Filling of cracked soils and rocks.
- Injection into bolt anchors.

#### **FEATURES**

- It expands the grout or mortar during the setting process, increasing adhesion, decreasing permeability, thus achieving perfect silting of the injected cavities and fissures.
- It has plasticizing and/or water reducing power.
- Prevents the formation of flocs by dispersing the cement particles in the aqueous suspension, achieving
  a better penetration of the pastes, mortars and grout
  into the cracks and cavities.
- Improves the durability of the paste, mortar and grout.
- Stabilizes the mixture by reducing exudation. Ligeramente Slightly delays setting, allowing injection at a greater distance.
- Assists in the corrosion protection of post-tensioned cables.
- Can be used with other water reducing additives, when a much lower a/c ratio is required.

# **PRODUCT INFORMATION**

Packaging	30 kg Bags
Appearance and colour	Yellowish gray powder with silver particles, mild odor
Shelf life	Six (6) months from its manufacturing date. Normal precautions for chem- ical products must be taken for transport.
Storage conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +35 °C. Always refer to packaging.
Density	1.25 kg/l +/- 0.05 kg/l

#### **APPLICATION INFORMATION**

Recommended dosage	It is dosed from 1.0% to 3.0% of the weight of the cement contained in the
	mixture.

PRODUCT DATA SHEET Sika® Intraplast® Z CO December 2024, Version 01.02 02130401100000071

# **BASIS OF PRODUCT DATA**

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### IMPORTANT CONSIDERATIONS

All technical data indicated in this technical sheet are based on laboratory tests. The actual measurements of this data may vary due to circumstances beyond our control.

# ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## **APPLICATION INSTRUCTIONS**

Sika<sup>®</sup> Intraplast<sup>®</sup> Z CO is added in the recommended dose of dry cement and mixes until a homogeneous material is obtained. Cement mixed with Sika<sup>®</sup> Intraplast<sup>®</sup> Z CO, can be added in the preparation of pastes, mortars, grouts or concrete.

# LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

# LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information. or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

PRODUCT DATA SHEET Sika® Intraplast® Z CO December 2024, Version 01.02 02130401100000071



**BUILDING TRUST** 

#### SIKA MANUFACTURING NIGERIA LIMITED

10,Western Industrial Avenue, Isheri Riverview Estate Lagos - Ibadan Expressway, Ogun State NIGERIA Web: nga.sika.com

PRODUCT DATA SHEET Sika® Intraplast® Z CO December 2024, Version 01.02 02130401100000071 SikaIntraplastZCO-en-NG-(12-2024)-1-2.pdf



**BUILDING TRUST**