

PRODUCT DATA SHEET

Sika[®] ViscoCrete[®]-1000 WP

Multi-purpose Superplasticizer / High Range Water-Reducing Admixture

DESCRIPTION

Sika ViscoCrete[®] 1000 WP is a new generation, non-chlorinated, acrylic copolymer superplasticizer / high-range water-reducing admixture.

USES

Sika ViscoCrete[®] 1000 WP combines several actions. Adsorption to the surface of the cement and separation of fines particles during the hydration process give the following properties :

- Very high water reduction (consequently high waterproofing and resistances).
- High fluidity (consequently easier application).
- High short term resistance.
- High waterproofing improvement.
- Better creeps and shrinkage behaviour.
- Lower carbonation speed.

Sika ViscoCrete[®] 1000 WP does not contain any chloride or other component which could cause or increase steel corrosion. It can be used without restriction for reinforced or prestressed concrete constructions.

FEATURES

Sika ViscoCrete[®] 1000 WP combines several actions. Adsorption to the surface of the cement and separation of fines particles during the hydration process give the following properties :

- Very high water reduction (consequently high waterproofing and resistances).
- High fluidity (consequently easier application).
- High short term resistance.

- High waterproofing improvement.
- Better creeps and shrinkage behaviour.
- Lower carbonation speed.

Sika ViscoCrete[®] 1000 WP does not contain any chloride or other component which could cause or increase steel corrosion. It can be used without restriction for reinforced or prestressed concrete constructions

CERTIFICATES AND TEST REPORTS

Sika[®] ViscoCrete[®] 1000 WP meets the requirements of NF EN 934-2 tables 3.1 & 3.2.

PRODUCT DATA SHEET

Sika[®] ViscoCrete[®]-1000 WP
February 2025, Version 01.03
021301011000004733

PRODUCT INFORMATION

Composition	PCE
Packaging	1000lts IBC 200lts drum 25lts kegs Bulk on request
Colour	Light Brown
Shelf life	12 months minimum from production date.
Storage conditions	The product must be stored in original,unopened and undamaged sealed packaging in dry conditions at temperature between 5°C and 35 °C. Protect away from direct sunlight.
Density	1.07 +/- 0.01
pH-Value	5 +/- 1
Recommended dosage	Recommended dosage: <ul style="list-style-type: none">▪ 0.2 to 3% of the cement weight depending on performances required.▪ Usual dosage: 0.4 to 1.5% of the binder weight.
Application time	Sika Viscocrete® 1000 WP is added either at the same time as the mixing water or at a later stage to concrete that has been pre-moistened with a part of the mixing water.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its

SIKA MANUFACTURING NIGERIA LIMITED

10, Western Industrial Avenue, Isheri
Riverview Estate
Lagos - Ibadan Expressway, Ogun State
NIGERIA
Web: nga.sika.com

PRODUCT DATA SHEET

Sika® ViscoCrete®-1000 WP
February 2025, Version 01.03
021301011000004733

