

## SYSTEM DATA SHEET

# Sikafloor® Terrazzo CS-32

A highly durable, decorative concrete flooring system, based on dry-shake hardeners, ground and polished to a class B (salt-and-pepper) finish

### DESCRIPTION

Sikafloor® Terrazzo CS-32 is a ground and polished concrete flooring system in which grinding fully exposes the fine dry-shake hardener, producing a class B "salt-and-pepper" surface. The patented method enables the application of multiple layers of dry shake. The specially-designed finishing aid provides a more reliable surface finishing, densifies, and improves surface hardness.

### USES

Sikafloor® Terrazzo CS-32 is used for:

- Medium to heavy wear new concrete floors

Sikafloor® Terrazzo CS-32 is used for the following application areas:

- Car park decks
- Commercial and public buildings
- Railway and metro stations
- Logistics facilities and warehouses
- Industrial buildings
- Electronic facilities and data centres

Please note:

- The System may only be used by experienced professionals.
- The System may only be used for interior applications.

### FEATURES

- Decorative class B ("salt-and-pepper") finish, fully exposing the dry-shake aggregate
- Polished to chosen sheen level
- High durability
- Wide range of colours available
- Light colours help improve natural lighting
- Cost-effective
- Separate liquid hardener not needed after application
- Low maintenance
- Reduced moisture loss in early phase
- Easy application and finishing
- Quality improved final finish
- Increased resistance to oils and grease

### CERTIFICATES AND TEST REPORTS

- Particle Emission ISO 14644-1, Sikafloor® Terrazzo CS-32, IPA Fraunhofer, Approval No. SI 2403-1509

## SYSTEM INFORMATION

System structure	Layer	Product												
	Dry shake hardener	Sikafloor®-3 QuartzTop Sikafloor®-3 QuartzTop Design Sikafloor®-2 SynTop Sika® Chapdur®												
	Finishing aid	Sikafloor®-931 Finishing Aid												
	Curing	Water, blankets, curing sheets or foils												
	Polishing	Grinding for full dry-shake aggregate exposure Polishing level 2, 3, or 4 for sheen												
	Seal coat	Sikagard®-915 Stainprotect Sikafloor®-958 PG (CZ)												
<b>Appearance</b>	<p>The class refers to the amount of aggregate exposed during grinding. Class B offers a salt-and-pepper finish by fully exposing the aggregate in the dry-shake hardener.</p> <p>The sheen level refers to the gloss of the polished floor, is measured using distinctness-of-image, and depends on the grit used during polishing.</p>													
	<table border="1"> <thead> <tr> <th>Sheen Level</th> <th>DOI reading</th> <th>Grit</th> </tr> </thead> <tbody> <tr> <td>Level 2 (Satin)</td> <td>10-39</td> <td>200-400</td> </tr> <tr> <td>Level 3 (Polished Gloss)</td> <td>40-69</td> <td>800-1000</td> </tr> <tr> <td>Level 4 (Very High Gloss)</td> <td>70-100</td> <td>1000-3000</td> </tr> </tbody> </table>	Sheen Level	DOI reading	Grit	Level 2 (Satin)	10-39	200-400	Level 3 (Polished Gloss)	40-69	800-1000	Level 4 (Very High Gloss)	70-100	1000-3000	
Sheen Level	DOI reading	Grit												
Level 2 (Satin)	10-39	200-400												
Level 3 (Polished Gloss)	40-69	800-1000												
Level 4 (Very High Gloss)	70-100	1000-3000												
<b>Colour</b>	Available in a range of colours. Please contact Sika customer service for availability.													
<b>Nominal thickness</b>	2.5-4 mm													

## APPLICATION INFORMATION

Consumption	Layer	Product	Consumption
	Dry shake hardener	Sikafloor®-3 QuartzTop Sikafloor®-3 QuartzTop Design Sikafloor®-2 SynTop Sika® Chapdur®	6-10 kg/m <sup>2</sup>
	Finishing aid	Sikafloor®-931 Finishing Aid	25-50 g/m <sup>2</sup> per application
	Seal coat	Sikagard®-915 Stainprotect Sikafloor®-958 PG (CZ)	15-90 g/m <sup>2</sup>

## PRODUCT INFORMATION

### Packaging

### Shelf life

### Storage conditions

## BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## FURTHER DOCUMENTATION

- Sika Method Statement 850 84 23 Sikafloor® EasyFinish CS-30, Sikafloor® CreamPolish CS-31, Sikafloor® Terrazzo CS-32
- Individual Product Data Sheets

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**SIKA MANUFACTURING NIGERIA LIMITED**  
10,Western Industrial Avenue, Isheri  
Riverview Estate  
Lagos - Ibadan Expressway, Ogun State  
NIGERIA  
Web: [nga.sika.com](http://nga.sika.com)

**SYSTEM DATA SHEET**  
Sikafloor® Terrazzo CS-32  
January 2026, Version 04.01  
02081590000000016

SikafloorTerrazzoCS-32-en-NG-(01-2026)-4-1.pdf

**BUILDING TRUST**

