

PRODUCT DATA SHEET

SikaGrind[®]-700

Grinding aid and quality improver for the production of cement

DESCRIPTION

SikaGrind[®]-700 is a chloride free, liquid cement additive.

USES

- Increase the production rate of cement
- Increase the early and final strength of cement

FEATURES

SikaGrind[®]-700 provides the following advantages in the cement production:

- Increased production rate
- Easier achievement of the desired cement fineness
- Cost savings due to lower specific power consumption per ton

SikaGrind[®]-700 provides the following advantages to the finished cement:

- Increased early strength
- Improved powder flow characteristics

CERTIFICATES AND TEST REPORTS

SikaGrind[®]-700 is produced in our factories under Quality management systems according to EN ISO 9001.

PRODUCT INFORMATION

Composition	Amines
Packaging	1000 kg IBC Bulk deliveries
Shelf life	At least 12 months shelf life from date of production if stored properly in undamaged, unopened, original sealed packaging.
Storage conditions	stored at temperatures between +5°C and +35°C. Protect from frost, direct sunlight and contamination. Note: When delivered in bulk, the tanks and equipment used must be free from contaminants.
Appearance and colour	Yellowish liquid
Density	1.09 ± 0.03 kg/l (at +20°C)
Viscosity	< 25 mPas (at +20°C)
pH-Value	6.0 - 9.0
Total chloride ion content	< 0.1 M%

PRODUCT DATA SHEET

SikaGrind[®]-700

August 2024, Version 01.02

021407021000000008

APPLICATION INFORMATION

Recommended dosage	Typical dosage rates of SikaGrind®-700 are between 0.3 - 0.5 kg per ton of cement (0.03% - 0.05% of total weight = cement clinker + additions). The optimum dosage to achieve the desired characteristics shall be determined in plant trials. Influencing factors are e.g. the properties of clinker, type of cement and other plant variables. For consistent results, SikaGrind®-700 must be accurately dispensed.
Dispensing	SikaGrind®-700 is added onto the clinker feed shortly before the mill entrance or directly into the grinding mill. Suitable dosage pumps with adjustable flow rates shall be used for accurate dosing. Note: Periodically, the end of the additive tube/hose shall be checked to ensure that it is not blocked!
Compatibility	Cements treated with SikaGrind®-700 are compatible in concretes produced with all commercial admixtures including air entrainers, water reducers, retarders and superplasticizers. The performance of concrete admixtures is not adversely affected by the use of SikaGrind®-700.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA MANUFACTURING NIGERIA LIMITED
10, Western Industrial Avenue, Isheri
Riverview Estate
Lagos - Ibadan Expressway, Ogun State
NIGERIA
Web: nga.sika.com

PRODUCT DATA SHEET
SikaGrind®-700
August 2024, Version 01.02
021407021000000008

SikaGrind-700-en-NG-(08-2024)-1-2.pdf

